


PARTS LIST	
1	MiniDim w/ring lugs
1	Installation Instructions Optional
4	Color Coded Spade terminals
1	Optional Reference panel label
1	STC Printout for logs
1	Optional Installatin Template
	Optional Placard
1	Knob
3 ea	6-32 screws, lock washer for terminals
2	Allen Wrenches
1 ea	9mm x .75 bushing nut. washer, lock washer

SPECIFICATIONS	
STC/PMA	SA01800SE/PQ2574NM
DO-160E Testing	SEC. 21: RFE (EMI)
Voltage Range	12 to 35 VDC
Maximum Current	10 A per Channel
Output Channels	1
Internal Temp Protected	+85 degrees C
Enclosure Material	Bayer FR110 Resin meets UL94
Weight	1 ounce (28g)
Warranty	One Year Limited
Storage Temperature	-40C to +100C
Internal Temp	+25 C at 10 A

DIMENSIONAL TOLERANCES		
Fractions	Decimal inches	Angles
+/- 1/32	.XX +/- .08	+/- 1 degree
	.XXX +/- .010	
	X +/- .1	

REVISION HISTORY				
ZONE	REV	DESCRIPTION	DATE	APPROVED
All	--	Initial	3/3/2013	JB

DRAWN JB	4/8/2013	 Seaton Engineering
CHECKED JC	4/10/2013	
QA		TITLE
MFG JB	4/10/2013	MaxDim Mini w/spade lugs
APPROVED JB	4/10/2013	SIZE
		B
		DWG NO
		9100-001-E
		REV
		--
		SCALE
		2 : 1
		SHEET 1 OF 1