


PARTS LIST	
1	MaxDim Mini w/ring lugs
1	Installation Instructions
4	Color Coded Ring terminals
1	Optional Reference panel label
1	STC Printout for logs
1	Optional Installatin Template
1	Optional Placard
2	Knob
4 ea	6-32 screws, lock washer for terminals
2	Allen Wrenches
3 ea	9 X 75 MM bushing nut, lock washer
2 ea	Washer

SPECIFICATIONS	
STC/PMA	SA01800SE/PQ2574NM
DO-160E Testing	SEC. 21: RFE (EMI)
Voltage Range	12 to 35 VDC
Maximum Current	10 A per Channel
Output Channels	2
Internal Temp Protected	+85 degrees C
Enclosure Material	Bayer FR110 Resin meets UL94
Weight	1 ounce (28g)
Warranty	One Year Limited
Storage Temperature	-40C to +100C
Internal Temp	+25 C at 10 A

DIMENSIONAL TOLERANCES		
Fractions	Decimals	Angles
+/- 1/32	.XX +/- .08	+/- 1 degree
	.XXX +/- .010	
	X +/- .1	

REVISION HISTORY				
ZONE	REV	DESCRIPTION	DATE	APPROVED
All	--	Initial	4/10/2013	JB

DRAWN JB CHECKED JC QA	4/8/2013  4/8/2013  4/8/2013	 <b>Seaton Engineering</b>	TITLE <b>9100-001-F MaxDim Mini w/ring lugs</b>	
MFG JB APPROVED JB	4/8/2013  4/8/2013		SIZE <b>B</b>	DWG NO <b>9100-001-F</b>
SCALE 2 : 1		SHEET 1 OF 1		